














1769

3130

3122

3190

3201

3126

3202

3119

3203

1203

2638

3204

3134

3205

2849

3120
TOLLERANZE DIMENSIONALI DEI TRAFILATI IN GOMMA SECONDO UNI ISO 3302


da mm	0,0	1,6	2,6	4,1	6,4	10,1	16,1	25,1	40,1	63,1
a	1,5	2,5	4,0	6,3	10,0	16,0	25,0	40,0	63,0	100,0
Classe										
E2	±0,25	±0,35	±0,40	±0,50	±0,70	±0,80	±1,00	±1,30	±1,60	±2,00




3125




3206




2331




3124




3207



3208



3129



3211

**REALIZZABILI IN VARIE DUREZZE E
CON MISURE VARIABILI SECONDO
L'ESIGENZA DEL CLIENTE**

TOLLERANZE DIMENSIONALI DEI TRAFILATI IN GOMMA SECONDO UNI ISO 3302

da mm a	0,0 1,5	1,6 2,5	2,6 4,0	4,1 6,3	6,4 10,0	10,1 16,0	16,1 25,0	25,1 40,0	40,1 63,0	63,1 100,0
Classe										
E2	±0,25	±0,35	±0,40	±0,50	±0,70	±0,80	±1,00	±1,30	±1,60	±2,00